



**BEAMZ**  
**MADE**  
**EAZY**

150.730\_150.732\_150.734 V1.0

**STARCOLOR SERIES**  
**QUICK **START** GUIDE**

# CONTROL MENU

If the display is in standby, unlock it:



MENU			DESCRIPTION
<b>ADDR</b>	A001-A512		DMX address setting
<b>CH--</b>	8CH	Internal program 1-9	8 DMX Channel mode
	4CH		4 DMX Channel mode
	10CH		10 DMX Channel mode
<b>AU--</b>	Au.01	T.(00-99)	Macro mode 1 from slow to fast
	Au.02		Macro mode 2 from slow to fast
	...		...
	Au.10		Macro mode 10 from slow to fast
<b>COLO</b>	r.(000-255)		Manual colour adjustment
	g.(000-255)		
	b.(000-255)		
	u.(000-255)		
	S.(0-20)		
<b>DI--</b>	nod.0		No dimmer curve
	nod.1		Dimmer curve
	nod.2		
	nod.3		
	nod.4		
<b>LOC</b>	ON		Enable or disable control menu locking
	OFF		
<b>TEMP</b>			Show the LED PCB temperature
<b>RSET</b>	No		Load factory settings
	Yes		

# DMX CHANNELS

## 4 CHANNELS

CHANNEL	FUNCTION	VALUE	DESCRIPTION
1		000-255	Red dimmer 0-100%
2	Colour	000-255	Green dimmer 0-100%
3		000-255	Blue dimmer 0-100%
4		000-255	White dimmer 0-100%

## 8 CHANNELS

CHANNEL	FUNCTION	VALUE	DESCRIPTION
1	Dimmer	000-255	Master dimmer 0-100%
2	Colour	000-255	Red dimmer 0-100%
3		000-255	Green dimmer 0-100%
4		000-255	Blue dimmer 0-100%
5		000-255	White dimmer 0-100%
6	Strobe	000-012	No function
		013-255	Strobe from slow to fast
7	Macro	000-050	No function
		051-100	Static colours
		101-109	Macro mode 1
		110-119	Macro mode 2
		...	
		190-199	Macro mode 10
		200-255	No function

Channel 8 when value 51-100 (CH7)

8	Colour selection	000-255	Static colour
		000-031	Red
		032-063	Green
		064-095	Blue
		096-127	White
		128-159	Red + Green
		160-191	Red + Blue
		192-223	Green + Blue
		224-255	Full on

Channel 8 when value 101-255 (CH7)

8	Macro speed	000-255	Macro speed
---	-------------	---------	-------------

## 10 CHANNELS

CHANNEL	FUNCTION	VALUE	DESCRIPTION
1	Dimmer	000-255	Master dimmer 0-100%
2	Colour	000-255	Red dimmer 0-100%
3		000-255	Green dimmer 0-100%
4		000-255	Blue dimmer 0-100%
5		000-255	White dimmer 0-100%
6	Program colour	000-010	No function
		011-030	Red 100%, Green 0-100%, Blue 0% White 0%
		031-050	Red 100-0%, Green 100%, Blue 0% White 0%
		051-070	Red 0%, Green 100%, Blue 0-100% White 0%
		071-090	Red 0%, Green 100-0%, Blue 100% White 0%
		091-110	Red 0-100%, Green 0%, Blue 100% White 0%
		111-130	Red 100%, Green 0%, Blue 100-0% White 0%
		131-150	Red 100%, Green 0-100%, Blue 0-100% White 0-100%
		151-170	Red 100-0%, Green 100-0%, Blue 100% White 100%
		171-200	Red 100%, Green 100%, Blue 100% White 100%
		201-205	Colour temperature 1
		206-210	Colour temperature 2
		211-215	Colour temperature 3
		216-220	Colour temperature 4
		221-225	Colour temperature 5
		226-230	Colour temperature 6
		231-235	Colour temperature 7
	236-240	Colour temperature 8	
	241-245	Colour temperature 9	
	246-250	Colour temperature 10	
	251-255	Colour temperature 11	
7	Strobe	000-013	No function
		014-255	Strom from slow to fast
8	Macro	000-020	No function
		021-030	Macro mode 1
		031-040	Macro mode 2
		041-050	Macro mode 3
		051-060	Macro mode 4
		061-070	Macro mode 5
		071-080	Macro mode 6
		081-090	Macro mode 7
		091-100	Macro mode 8
		101-110	Macro mode 9
		111-120	Macro mode 10
	121-255	No function	
9	Macro speed	000-255	Speed from slow to fast
10	Dimmer curve	000-005	Depend on the operation setup
		006-055	No dimmer curve
		056-105	Dimmer curve 1
		106-155	Dimmer curve 2
		156-205	Dimmer curve 3
		206-255	Dimmer curve 4



A series of horizontal dotted lines for writing, spanning the width of the page.



A series of horizontal dotted lines spanning the width of the page, intended for handwriting practice.





A series of horizontal dotted lines for writing, spanning the width of the page.



# BEAMZ

**YOUR FUTURE**  
**YOUR SKILLS**  
**YOUR PLATFORM**  
**YOUR PARTY**  
**YOUR EVENT**



offers a wide range of high performance lighting equipment and related accessories for the rental, entertainment and architectural lighting markets. BeamZ Pro stands for performance, innovation and value pricing!

