



BEAMZ
MADE
EAZY

150.736 V1.0

STARCOLOR205

QUICK START GUIDE

CONTROL MENU

If the display is in standby, unlock it:



MENU	DESCRIPTION	
ADDR	A001-A512	DMX address setting
CH--	8CH	Internal program 1-9 8 DMX Channel mode
	4CH	4 DMX Channel mode
	10CH	10 DMX Channel mode
AU--	Au.01	T.(00-99) Macro mode 1 from slow to fast
	Au.02	Macro mode 2 from slow to fast

	Au.10	Macro mode 10 from slow to fast
COLO	r.(000-255)	Manual colour adjustment
	g.(000-255)	
	b.(000-255)	
	u.(000-255)	
	S.(0-20)	
DI--	nod.0	No dimmer curve
	nod.1	Dimmer curve
	nod.2	
	nod.3	
	nod.4	
LOC	ON	Enable or disable control menu locking
	OFF	
TEMP		Show the LED PCB temperature
RSET	No	Load factory settings
	Yes	

DMX CHANNELS

4 CHANNELS

CHANNEL	FUNCTION	VALUE	DESCRIPTION
1	COLOUR	000-255	Red dimmer 0-100%
2		000-255	Green dimmer 0-100%
3		000-255	Blue dimmer 0-100%
4		000-255	Amber dimmer 0-100%

8 CHANNELS

CHANNEL	FUNCTION	VALUE	DESCRIPTION
1	DIMMER	000-255	Master dimmer 0-100%
2	COLOUR	000-255	Red dimmer 0-100%
3		000-255	Green dimmer 0-100%
4		000-255	Blue dimmer 0-100%
5		000-255	Amber dimmer 0-100%
6		STROBE	000-012
	013-255		Strobe from slow to fast
7	MACRO	000-050	No function
		051-100	Static colours
		101-109	Macro mode 1
		110-119	Macro mode 2
	
		190-199	Macro mode 10
		200-255	No function

Channel 8 when value 51-100 (CH7)

8	COLOUR SELECTION	000-255	Static colour
		000-031	Red
		032-063	Green
		064-095	Blue
		096-127	Amber
		128-159	Red + Green
		160-191	Red + Blue
		192-223	Green + Blue
		224-255	Full on

Channel 8 when value 101-255 (CH7)

8	MACRO SPEED	000-255	Macro speed
---	-------------	---------	-------------

10 CHANNELS

CHANNEL	FUNCTION	VALUE	DESCRIPTION
1	DIMMER	000-255	Master dimmer 0-100%
2	COLOUR	000-255	Red dimmer 0-100%
3		000-255	Green dimmer 0-100%
4		000-255	Blue dimmer 0-100%
5		000-255	Amber dimmer 0-100%
6		PROGRAM COLOUR	000-010
	011-030		Red 100%, Green 0-100%, Blue 0% Amber 0%
	031-050		Red 100-0%, Green 100%, Blue 0% Amber 0%
	051-070		Red 0%, Green 100%, Blue 0-100% Amber 0%
	071-090		Red 0%, Green 100-0%, Blue 100% Amber 0%
	091-110		Red 0-100%, Green 0%, Blue 100% Amber 0%
	111-130		Red 100%, Green 0%, Blue 100-0% Amber 0%
	131-150		Red 100%, Green 0-100%, Blue 0-100% Amber 0-100%
	151-170		Red 100-0%, Green 100-0%, Blue 100% Amber 100%
	171-200		Red 100%, Green 100%, Blue 100% Amber 100%
	201-205		Colour temperature 1
	206-210		Colour temperature 2
	211-215		Colour temperature 3
	216-220		Colour temperature 4
	221-225		Colour temperature 5
	226-230		Colour temperature 6
	231-235		Colour temperature 7
	236-240		Colour temperature 8
	241-245		Colour temperature 9
	246-250		Colour temperature 10
	251-255		Colour temperature 11
7	STROBE	000-013	No function
		014-255	Strom from slow to fast
8	MACRO	000-020	No function
		021-030	Macro mode 1
		031-040	Macro mode 2
		041-050	Macro mode 3
		051-060	Macro mode 4
		061-070	Macro mode 5
		071-080	Macro mode 6
		081-090	Macro mode 7
		091-100	Macro mode 8
		101-110	Macro mode 9
		111-120	Macro mode 10
	121-255	No function	
9	MACRO SPEED	000-255	Speed from slow to fast
10	DIMMER CURVE	000-005	Depend on the operation setup
		006-055	No dimmer curve
		056-105	Dimmer curve 1
		106-155	Dimmer curve 2
		156-205	Dimmer curve 3
	206-255	Dimmer curve 4	



A series of horizontal dotted lines for writing, spanning the width of the page.



A series of horizontal dotted lines spanning the width of the page, intended for handwriting practice.





A series of horizontal dotted lines for writing, spanning the width of the page.



BEAMZ

YOUR FUTURE
YOUR SKILLS
YOUR PLATFORM
YOUR PARTY
YOUR EVENT



offers a wide range of high performance lighting equipment and related accessories for the rental, entertainment and architectural lighting markets. BeamZ Pro stands for performance, innovation and value pricing!

